NSN 5962-01-112-5700

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-112-5700

| Body Length: |
|--|
| Between 0.660 inches and 0.785 inches |
| Body Width: |
| Between 0.220 inches and 0.280 inches |
| Body Height: |
| Between 0.140 inches and 0.185 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs and high speed |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| P-type metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 2 driver, clock |
| Case Outline Source And Designator: |
| T0-116 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.5 volts power source |
| Time Rating Per Chacteristic: |
| 15.00 nanoseconds propagation delay time, low to high level output and 12.00 nanoseconds propagation delay time, high to low level |
| output |
| Terminal Type And Quantity: |
| 14 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| |

Fiig:

A458a0