NSN 5962-01-112-7070

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-112-7070
Body Length:
Between 0.755 inches and 0.785 inches
Body Width:
Between 0.245 inches and 0.280 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
195.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Computer system, digital an/uyk-47
Features Provided:
Hermetically sealed and bidirectional and w/clock and w/clear
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
10 input
Design Function And Quantity:
1 shift register, universal
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
22.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
16 printed circuit
Specification Data:
07421-349-900 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: Yes - demil/mli

NSN 5962-01-112-7070

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0