NSN 5962-01-112-7398

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-112-7398

View Online at https://aerobasegroup.com/nsn/5962-01-112-7398
Body Length:
Between 1.030 inches and 1.090 inches
Body Width:
Between 0.600 inches and 0.660 inches
Body Height:
Between 0.070 inches and 0.115 inches
Maximum Power Dissipation Rating:
1.6 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
13 input
Design Function And Quantity:
1 arithmetic logic unit
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
110.00 nanoseconds propagation delay time, low to high level output and 110.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
42 flat leads
Specification Data:
81349-mil-m-38510/440/usaf/ government specification
Shelf Life:

Demilitarization:

Unit Of Measure:

N/a

NSN 5962-01-112-7398

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0