## NSN 5962-01-113-6173

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-113-6173

Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
750.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and w/switch
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Input Circuit Pattern:
4 channel
Design Function And Quantity:
4 switch, analog
Case Outline Source And Designator:
D-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
32.0 volts power source
Time Rating Per Chacteristic:
650.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low leve
output
Test Data Document:
14933-77053 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig: