NSN 5962-01-115-2150

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-115-2150

Body Length:
1.290 inches
Body Width:
Between 0.515 inches and 0.560 inches
Body Height:
0.205 inches
Maximum Power Dissipation Rating:
1.1 watts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and darlington-connected and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
input on out 1 attorn.
14 input
14 input
14 input Design Function And Quantity:
14 input Design Function And Quantity: 1 arithmetic logic unit
14 input Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic:
14 input Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute
14 input Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment:
14 input Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder
14 input Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
14 input Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source
Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Time Rating Per Chacteristic:
Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Time Rating Per Chacteristic: 30.00 nanoseconds delay
Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Time Rating Per Chacteristic: 30.00 nanoseconds delay Terminal Type And Quantity:
Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Time Rating Per Chacteristic: 30.00 nanoseconds delay Terminal Type And Quantity: 24 printed circuit
Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Time Rating Per Chacteristic: 30.00 nanoseconds delay Terminal Type And Quantity: 24 printed circuit Shelf Life:
Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Time Rating Per Chacteristic: 30.00 nanoseconds delay Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a
Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Time Rating Per Chacteristic: 30.00 nanoseconds delay Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a
Design Function And Quantity: 1 arithmetic logic unit Current Rating Per Characteristic: 220.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Time Rating Per Chacteristic: 30.00 nanoseconds delay Terminal Type And Quantity: 24 printed circuit Shelf Life: N/a Unit Of Measure:

. ..9

A458a0