NSN 5962-01-115-7572



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-115-7572 **Body Length:** 0.785 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and w/resistor and w/enable and hermetically sealed and burn in **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 2 switch, analog, single pole single throw normally open **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Solder **Time Rating Per Chacteristic:** 2500.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0