

View Online at <https://aerobasegroup.com/nsn/5962-01-116-1996>

Body Length:

0.840 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.140 inches and 0.185 inches

Maximum Power Dissipation Rating:

220.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and negative outputs and w/enable

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Dual 3 input

Design Function And Quantity:

2 driver, line

Case Outline Source And Designator:

D-2 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

28.00 nanoseconds propagation delay time, low to high level output and 28.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

14933-80041 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0