## NSN 5962-01-116-5787

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-116-5787

| Body Length:   |
|--|
| 0.785 inches   |
| Body Width:  |
| Between 0.220 inches and 0.310 inches                                  |
| Body Height:   |
| Between 0.140 inches and 0.185 inches                                  |
| Maximum Power Dissipation Rating:                                      |
| 440.0 milliwatts   |
| Operating Tempurature Range:   |
| -30.0/+85.0 degrees celsius  |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| End Application:   |
| Tafts 82577  |
| Features Provided:   |
| Hermetically sealed and monolithic and positive outputs and high speed |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Output Logic Form:   |
| Emitter-coupled logic  |
| Input Circuit Pattern:   |
| Triple 2 input   |
| Design Function And Quantity:  |
| 3 gate, exclusive nor  |
| Case Outline Source And Designator:                                    |
| D-1 mil-m-38510  |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:                            |
| -8.0 volts power source and 0.0 volts power source                     |
| Terminal Type And Quantity:  |
| 16 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |