NSN 5962-01-116-8667

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-116-8667

Body Length:
0.785 inches
Body Width:
0.250 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
150.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
F16maintntrng 81755
Features Provided:
Hermetically sealed and monolithic and w/strobe
Inclosure Material:
Ceramic
nclosure Configuration:
Dual-in-line
Output Logic Form:
ransistor-transistor logic
nput Circuit Pattern:
0 input
Design Function And Quantity:
2 selector, data, two to one line
Terminal Surface Treatment:
Solder
/oltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
23.00 nanoseconds propagation delay time, low to high level output and 27.00 nanoseconds propagation delay time, high to low leve
output
Test Data Document:
15280-48-038166 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawin
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

NSN 5962-01-116-8667 Digital Microcircuit - Page 2 of 2

Fiig: A458a0

