## NSN 5962-01-117-1378

Linear Microcircuit - Page 1 of 1



7-1378

| View Online at https://aerobasegroup.com/nsn/5962-01-117 |
|--|
| Body Outside Diameter:                                   |
| Between 0.335 inches and 0.370 inches                    |
| Body Height:   |
| Between 0.165 inches and 0.185 inches                    |
| Maximum Power Dissipation Rating:                        |
| 300.0 milliwatts   |
| Operating Tempurature Range:                             |
| -55.0/+125.0 degrees celsius                             |
| Storage Tempurature Range:                               |
| -65.0/+150.0 degrees celsius                             |
| End Application:   |
| F16aircombfit 81755                                      |
| Features Provided:                                       |
| Hermetically sealed and monolithic and positive outputs  |
| Inclosure Material:                                      |
| Glass and metal  |
| Inclosure Configuration:                                 |
| Can  |
| Input Circuit Pattern:                                   |
| 2 input  |
| Design Function And Quantity:                            |
| 1 reference, voltage, analog                             |
| Case Outline Source And Designator:                      |
| T0-99 joint electron device engineering council          |
| Terminal Surface Treatment:                              |
| Tin  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |