## NSN 5962-01-117-2594

Digital Microcircuit - Page 1 of 1

Demilitarization: Yes - demil/mli

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-117-2594 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and monolithic and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Quad 3-2-2-3 input **Design Function And Quantity:** 4 gate, nand **Case Outline Source And Designator:** D-2 mil-m-38510 **Time Rating Per Chacteristic:** 300.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a **Unit Of Measure:**