# NSN 5962-01-117-8551

Digital Microcircuit - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5962-01-117-8551



## **Body Length:**

1.000 inches

## Body Width:

Between 0.220 inches and 0.300 inches

## **Body Height:**

Between 0.160 inches and 0.205 inches

## **Maximum Power Dissipation Rating:**

220.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### End Application:

F/tf-15a actf fscm 76301

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and low power and schottky

#### **Inclosure Material:**

Ceramic and glass

## Inclosure Configuration:

Dual-in-line

#### Output Logic Form:

Transistor-transistor logic

#### Input Circuit Pattern:

14 input

#### **Design Function And Quantity:**

1 comparator

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

5.5 volts power source

#### **Time Rating Per Chacteristic:**

15.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level

## output

### **Test Data Document:**

07187-4034813 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Terminal Type And Quantity:

20 printed circuit

## Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

# NSN 5962-01-117-8551

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

