## NSN 5962-01-118-7537

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-118-7537 **Body Length:** 0.870 inches **Body Width:** 0.280 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 400.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 2350-01-080-9087 80064 **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/clear **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 1 latch, addressable **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 18.5 volts power source **Time Rating Per Chacteristic:** 80.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 80064-2618749 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a

**Demilitarization:** Yes - demil/mli

**Unit Of Measure:** 

## NSN 5962-01-118-7537

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0