NSN 5962-01-119-2965

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-119-2965 **Body Length:** 0.785 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 400.0 milliwatts **Operating Tempurature Range:** -55.0/+150.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Torpedo mk48 05825 **Features Provided:** Hermetically sealed and monolithic and positive outputs and internally compensated **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 amplifier, operational, general purpose **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -20.0 volts power source and 20.0 volts power source **Time Rating Per Chacteristic:** 800.00 nanoseconds propagation delay time, low to high level output and 800.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:**

Fiig:

A458a0

Demilitarization: Yes - demil/mli