NSN 5962-01-119-3881

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-119-3881

| Body Length: |
|--|
| 0.875 inches |
| Body Width: |
| 0.250 inches |
| Body Height: |
| Between 0.140 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and w/enable |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 6 input |
| Design Function And Quantity: |
| 4 latch, d |
| Case Outline Source And Designator: |
| D-2 mil-m-38510 |
| Current Rating Per Characteristic: |
| 1.00 microamperes supply |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 18.5 volts power source |
| Test Data Document: |
| 14933-81019 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

NSN 5962-01-119-3881

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

