NSN 5962-01-119-4694

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-119-4694

| Body Length: |
|----------------------------------------------------------------------------------------------------|
| Between 0.770 inches and 0.810 inches |
| Body Width: |
| Between 0.280 inches and 0.300 inches |
| Body Height: |
| Between 0.060 inches and 0.120 inches |
| Maximum Power Dissipation Rating: |
| 670.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| 4920-01-094-8835 03640 |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs and low power and programmable and bipolar |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| 5 input |
| Design Function And Quantity: |
| 1 converter |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.0 volts power source and 15.0 volts power source |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |