

View Online at <https://aerobasegroup.com/nsn/5962-01-119-4706>

Body Length:

Between 1.340 inches and 1.400 inches

Body Width:

Between 0.515 inches and 0.560 inches

Body Height:

Between 0.120 inches and 0.165 inches

Maximum Power Dissipation Rating:

550.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-55.0/+150.0 degrees celsius

End Application:

2350-01-080-9087 fscm 80064

Features Provided:

Hermetically sealed and monolithic and positive outputs and asynchronous and bidirectional and resettable and synchronous and w/enable

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

N-type metal oxide-semiconductor logic

Input Circuit Pattern:

14 input

Design Function And Quantity:

1 timer

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.3 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

320.00 nanoseconds propagation delay time, low to high level output and 320.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

80064-2618714 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0