

View Online at <https://aerobasegroup.com/nsn/5962-01-119-4706>

**Body Length:**

Between 1.340 inches and 1.400 inches

**Body Width:**

Between 0.515 inches and 0.560 inches

**Body Height:**

Between 0.120 inches and 0.165 inches

**Maximum Power Dissipation Rating:**

550.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-55.0/+150.0 degrees celsius

**End Application:**

2350-01-080-9087 fscm 80064

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and asynchronous and bidirectional and resettable and synchronous and w/enable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

N-type metal oxide-semiconductor logic

**Input Circuit Pattern:**

14 input

**Design Function And Quantity:**

1 timer

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.3 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

320.00 nanoseconds propagation delay time, low to high level output and 320.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

80064-2618714 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

28 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0