

View Online at <https://aerobasegroup.com/nsn/5962-01-119-6664>

**Body Length:**

Between 0.745 inches and 0.755 inches

**Body Width:**

Between 0.245 inches and 0.252 inches

**Body Height:**

Between 0.115 inches and 0.125 inches

**Maximum Power Dissipation Rating:**

333.0 milliwatts

**Operating Temperature Range:**

+0.0/+75.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Ts-3852 v2g e/i fscm 80058

**Features Provided:**

Monolithic and bipolar and expandable and positive outputs and w/enable and 3-state output

**Inclosure Material:**

Plastic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

6 input

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-1.5 volts power source and 5.5 volts power source

**Time Rating Per Characteristic:**

65.00 nanoseconds propagation delay time, low to high level output and 65.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Rom

**Test Data Document:**

50621-021-0005 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0