

View Online at <https://aerobasegroup.com/nsn/5962-01-119-6664>

Body Length:

Between 0.745 inches and 0.755 inches

Body Width:

Between 0.245 inches and 0.252 inches

Body Height:

Between 0.115 inches and 0.125 inches

Maximum Power Dissipation Rating:

333.0 milliwatts

Operating Temperature Range:

+0.0/+75.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Ts-3852 v2g e/i fscm 80058

Features Provided:

Monolithic and bipolar and expandable and positive outputs and w/enable and 3-state output

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

6 input

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

Time Rating Per Characteristic:

65.00 nanoseconds propagation delay time, low to high level output and 65.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Rom

Test Data Document:

50621-021-0005 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0