

View Online at <https://aerobasegroup.com/nsn/5962-01-119-7551>

Body Length:

Between 0.755 inches and 0.785 inches

Body Width:

Between 0.245 inches and 0.280 inches

Body Height:

Between 0.140 inches and 0.180 inches

Maximum Power Dissipation Rating:

60.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Md-1118/v1-g fscm 80058

Features Provided:

Hermetically sealed and monolithic and positive outputs and edge triggered and low power and schottky

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

3 input

Design Function And Quantity:

1 shift register, serial in, serial out

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

Time Rating Per Characteristic:

40.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0