NSN 5962-01-119-7553

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-119-7553

| Body Length: |
|-----------------------------------------------------------------------------------------------------|
| 0.840 inches |
| Body Width: |
| Between 0.220 inches and 0.310 inches |
| Body Height: |
| Between 0.140 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 100.0 milliwatts |
| Operating Tempurature Range: |
| +0.0/+75.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| 4920-01-094-8835 03640 |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs and high speed and low power and w/resistor |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Emitter-coupled logic |
| Input Circuit Pattern: |
| Quad 2 input |
| Design Function And Quantity: |
| 4 gate, or |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -8.0 volts power source and 0.0 volts power source |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |