NSN 5962-01-119-8522

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-119-8522

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.165 inches and 0.185 inches

Maximum Power Dissipation Rating:

350.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Nav sys 26512

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs

Inclosure Material:

Metal

Inclosure Configuration:

Can

Input Circuit Pattern:

1 input

Design Function And Quantity:

1 amplifier, operational, video follower

Case Outline Source And Designator:

A-1 mil-m-38510

Terminal Surface Treatment:

Gold

Time Rating Per Chacteristic:

44.00 nanoseconds propagation delay time, low to high level output

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-38510/106 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5962-01-119-8522

Linear Microcircuit - Page 2 of 2

Fiig: A458a0

