## NSN 5962-01-120-0963



Linear Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-120-0963 **Body Length:** 0.870 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.140 inches and 0.180 inches **Maximum Power Dissipation Rating:** 1150.0 milliwatts **Operating Tempurature Range:** -25.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Md-1118/v1-g fscm 80058 **Features Provided:** Monolithic and positive outputs and adjustable and bipolar and high speed **Inclosure Material:** Plastic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 1 input **Design Function And Quantity:** 2 switch, double pole single throw normally closed **Terminal Surface Treatment:** Silver **Voltage Rating And Type Per Characteristic:** 33.0 volts power source **Time Rating Per Chacteristic:** 175.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface silver **Precious Material:** Silver **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a

Demilitarization:

**Unit Of Measure:** 

Yes - demil/mli

## NSN 5962-01-120-0963

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0