NSN 5962-01-120-1244

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/psp/5062-01-120-1244

| View Online at https://aerobasegroup.com/nsn/5962-01-120-1244 |
|--------------------------------------------------------------------------------------------------|
| Body Outside Diameter: |
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| F/tf-15a aircraft 76301 |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs and low noise and internally compensated |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Can |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 6 input |
| Design Function And Quantity: |
| 2 multiplier and 1 divider/squarer/square rooter |
| Case Outline Source And Designator: |
| T0-100 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -20.0 volts power source and 20.0 volts power source |
| Terminal Type And Quantity: |
| 10 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |

A458a0