## NSN 5962-01-120-1266

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-120-1266
Body Length:
Between 0.750 inches and 0.785 inches
Body Width:
Between 0.240 inches and 0.295 inches
Body Height:
Between 0.160 inches and 0.180 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
4920-01-054-8585 81755
Features Provided:
Hermetically sealed and high impedance and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
9 input
Design Function And Quantity:
4 latch, nor, r/s
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 18.5 volts power source
Time Rating Per Chacteristic:
350.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
16340-60-00014 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

**Fiig:** A458a0

No