NSN 5962-01-120-9328

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-120-9328

Between 0.710 inches and 0.770 inches Body Width: Between 0.240 inches and 0.260 inches Body Height: Between 0.140 inches and 0.180 inches Operating Tempurature Range:
Body Width: Between 0.240 inches and 0.260 inches Body Height: Between 0.140 inches and 0.180 inches Operating Tempurature Range:
Between 0.240 inches and 0.260 inches Body Height: Between 0.140 inches and 0.180 inches Operating Tempurature Range:
Body Height: Between 0.140 inches and 0.180 inches Operating Tempurature Range:
Between 0.140 inches and 0.180 inches Operating Tempurature Range:
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-55.0/+150.0 degrees celsius
End Application:
Mu-696/u fscm 11530
Features Provided:
Monolithic and positive outputs and w/strobe
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
7 input
Design Function And Quantity:
2 receiver, line
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A458a0