

View Online at <https://aerobasegroup.com/nsn/5962-01-120-9329>

**Body Length:**

Between 0.770 inches and 0.810 inches

**Body Width:**

Between 0.280 inches and 0.300 inches

**Body Height:**

Between 0.060 inches and 0.120 inches

**Maximum Power Dissipation Rating:**

900.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

4120-01-047-3950 18323

**Features Provided:**

Compatible cmos and dielectric isolated and electrostatic sensitive and hermetically sealed and w/switch

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

4 channel

**Design Function And Quantity:**

4 switch, analog, single pole single throw normally open

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

-40.0 volts power source and 40.0 volts power source

**Time Rating Per Characteristic:**

500.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0