

View Online at <https://aerobasegroup.com/nsn/5962-01-120-9332>

**Body Length:**

Between 0.745 inches and 0.755 inches

**Body Width:**

Between 0.245 inches and 0.252 inches

**Body Height:**

Between 0.115 inches and 0.125 inches

**Maximum Power Dissipation Rating:**

300.0 milliwatts

**Operating Temperature Range:**

+0.0/+70.0 degrees celsius

**Storage Temperature Range:**

-65.0/+175.0 degrees celsius

**End Application:**

4920-01-065-4907 fscm 81205

**Features Provided:**

Monolithic and positive outputs and high speed and programmable and schottky

**Inclosure Material:**

Plastic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

4 input

**Design Function And Quantity:**

1 decoder, one of eight line

**Case Outline Source And Designator:**

To-116 joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-1.5 volts power source and 5.5 volts power source

**Time Rating Per Characteristic:**

16.00 nanoseconds propagation delay time, low to high level output and 16.00 nanoseconds propagation delay time, high to low level output

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0