

View Online at <https://aerobasegroup.com/nsn/5962-01-120-9332>

Body Length:

Between 0.745 inches and 0.755 inches

Body Width:

Between 0.245 inches and 0.252 inches

Body Height:

Between 0.115 inches and 0.125 inches

Maximum Power Dissipation Rating:

300.0 milliwatts

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Storage Temperature Range:

-65.0/+175.0 degrees celsius

End Application:

4920-01-065-4907 fscm 81205

Features Provided:

Monolithic and positive outputs and high speed and programmable and schottky

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

4 input

Design Function And Quantity:

1 decoder, one of eight line

Case Outline Source And Designator:

To-116 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

Time Rating Per Characteristic:

16.00 nanoseconds propagation delay time, low to high level output and 16.00 nanoseconds propagation delay time, high to low level output

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0