NSN 5962-01-121-7960

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-121-7960

Body Length:
Between 0.750 inches and 0.785 inches
Body Width:
Between 0.245 inches and 0.271 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
An/wlq- (v) 07397
Features Provided:
Burn in, mil-std-883, class b and hermetically sealed and high speed and w/strobe
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Triple 4-3-4 input
Design Function And Quantity:
3 receiver, line
Terminal Surface Treatment:
Tin
Time Rating Per Chacteristic:
30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0