

View Online at <https://aerobasegroup.com/nsn/5962-01-121-9610>

**Body Length:**

0.785 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

24.4 milliwatts

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Storage Temperature Range:**

-65.0 to 150.0 degrees celsius

**End Application:**

Gmsrsmodkit12 81205

**Features Provided:**

Burn in and hermetically sealed and low power and monolithic and schottky

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Quad 2 input

**Design Function And Quantity:**

4 gate, nand

**Case Outline Source And Designator:**

D-1 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

20.00 nanoseconds propagation delay time, low to high level output and 24.00 nanoseconds propagation delay time, high to low level output

**Special Features:**

Nuclear hardness critical item

**Nuclear Hardness Critical Feature:**

Hardened

**Test Data Document:**

81205-280-22065 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0