

View Online at <https://aerobasegroup.com/nsn/5962-01-122-2626>

Body Length:

1.290 inches

Body Width:

Between 0.515 inches and 0.525 inches

Body Height:

Between 0.130 inches and 0.180 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

4920-01-054-8585 81755

Features Provided:

Hermetically sealed and low power and w/storage

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

4 input

Design Function And Quantity:

1 register, successive approximation

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

16.3 volts power source

Time Rating Per Characteristic:

350.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0