## NSN 5962-01-122-6981

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-122-6981 **Body Length:** 0.420 inches **Body Width:** 0.390 inches **Body Height:** 0.076 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** F16maintntrng 81755 **Features Provided:** Hermetically sealed and monolithic and bipolar and w/enable and 3-state output and programmed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 14 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts total supply **Time Rating Per Chacteristic:** 250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Prom **Test Data Document:** 88818-a574a137 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 24 flat leads Shelf Life: N/a **Unit Of Measure:** 

**Fiig:** A458a0

**Demilitarization:** Yes - demil/mli