NSN 5962-01-122-7304

Digital Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-122-7304

View Online at https://aerobasegroup.com/nsn/5962-01-122-7304
Body Length:
Between 0.740 inches and 0.870 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.200 inches
Operating Tempurature Range:
55.0/+125.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
End Application:
F-16 81755
Features Provided:
Hermetically sealed and schottky and monolithic
nclosure Material:
Ceramic
nclosure Configuration:
Dual-in-line
Output Logic Form:
Emitter-coupled logic
nput Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 translator, ecl to ttl
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
6.00 nanoseconds propagation delay time, low to high level output and 6.00 nanoseconds propagation delay time, high to low level output
Test Data Document:
12436-6010343 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Eija·