

View Online at <https://aerobasegroup.com/nsn/5962-01-122-7304>

Body Length:

Between 0.740 inches and 0.870 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.200 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

F-16 81755

Features Provided:

Hermetically sealed and schottky and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Emitter-coupled logic

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 translator, ecl to ttl

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

6.00 nanoseconds propagation delay time, low to high level output and 6.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

12436-6010343 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0