# NSN 5962-01-122-7624

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-122-7624

## **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

## **Body Height:**

Between 0.165 inches and 0.185 inches

# Maximum Power Dissipation Rating:

630.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

Mx9730/aas35v 04939

#### **Features Provided:**

Bipolar and high impedance and high slew rate and internally compensated and w/strobe

#### Inclosure Material:

Metal

### Inclosure Configuration:

Can

### **Input Circuit Pattern:**

2 input

### **Design Function And Quantity:**

1 amplifier, operational, general purpose

## **Case Outline Source And Designator:**

T0-5 joint electron device engineering council

## **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

36.0 volts power source

### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

### Terminal Type And Quantity:

8 pin

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0