## NSN 5962-01-122-7627

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-122-7627

Body Le	ngth:
Between	0.755

Between 0.755 inches and 0.785 inches

**Body Width:** 

Between 0.265 inches and 0.291 inches

**Body Height:** 

Between 0.150 inches and 0.199 inches

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

## **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

**End Application:** 

4920-01-088-1061 35351

**Features Provided:** 

Hermetically sealed and monolithic and complementary outputs and wire-or outputs

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Dual-in-line

**Output Logic Form:** 

Transistor-transistor logic

**Input Circuit Pattern:** 

Dual 3 input

**Design Function And Quantity:** 

2 driver, line differential

**Terminal Surface Treatment:** 

Gold

**Voltage Rating And Type Per Characteristic:** 

5.5 volts power source

**Time Rating Per Chacteristic:** 

20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:** 

Terminal surface gold

**Precious Material:** 

Gold

**Test Data Document:** 

35351-151595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

16 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

-

## NSN 5962-01-122-7627

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0