# NSN 5962-01-123-2462

Linear Microcircuit - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5962-01-123-2462

# Body Outside Diameter:

0.370 inches

### **Body Height:**

0.185 inches

## **Maximum Power Dissipation Rating:**

300.0 milliwatts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

4920nc399071g 81755

### **Features Provided:**

Hermetically sealed and monolithic and high slew rate

#### Inclosure Material:

Metal

### Inclosure Configuration:

Can

### Input Circuit Pattern:

2 input

### **Design Function And Quantity:**

1 amplifier, operational, general purpose

# **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

15.0 volts power source

### **Test Data Document:**

15786-303146 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Terminal Type And Quantity:

8 pin

## Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

Fiig:

A458a0

