## NSN 5962-01-123-2465

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-123-2465

Body Outside Diameter:
Between 0.550 inches and 0.650 inches
Body Height:
Between 0.270 inches and 0.330 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Radar 76301
Features Provided:
Hermetically sealed and monolithic and bipolar
Inclosure Material:
Metal
Inclosure Configuration:
Can
Output Logic Form:
Metal oxide-semiconductor logic
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 driver, clock
Case Outline Source And Designator:
T0-8 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
22.0 volts power source
Time Rating Per Chacteristic:
35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
82577-932710 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
12 pin
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Vas - demil/mli

**Fiig:** A458a0