NSN 5962-01-123-3153

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-123-3153

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
4920-01-094-8835 03640
Features Provided:
Hermetically sealed and high voltage and high current
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 driver, peripheral
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
65.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A458a0