## NSN 5962-01-123-3156



Linear Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-123-3156 **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 400.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Radar 76301 **Features Provided:** Hermetically sealed and monolithic and high impedance and 3-state output **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 2 driver, line differential **Case Outline Source And Designator:** F-5 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 82577-932822 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 

16 flat leads

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

## NSN 5962-01-123-3156

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0