

View Online at <https://aerobasegroup.com/nsn/5962-01-123-4783>

Body Length:

Between 0.355 inches and 0.400 inches

Body Width:

Between 0.355 inches and 0.400 inches

Body Height:

0.090 inches

Maximum Power Dissipation Rating:

175.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and bipolar and burn in, mil-std-883, class b and electrostatic sensitive and programmable and w/buffered output and 3-state output

Inclosure Material:

Glass and metal

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

12 input

Terminal Surface Treatment:

Solder or gold

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

Time Rating Per Characteristic:

75.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Rom

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Test Data Document:

82577-932883 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

18 flat leads

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fig:

A458a0