

View Online at <https://aerobasegroup.com/nsn/5962-01-123-6645>

**Body Length:**

Between 0.590 inches and 0.625 inches

**Body Width:**

Between 0.360 inches and 0.400 inches

**Body Height:**

Between 0.050 inches and 0.085 inches

**Maximum Power Dissipation Rating:**

910.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Radar set fscm 76301

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and bipolar and expandable and high speed and w/enable and 3-state output

**Inclosure Material:**

Glass and metal

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

17 input

**Current Rating Per Characteristic:**

140.00 milliamperes supply

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

7.0 volts power source

**Capitance Rating Per Characteristic:**

4.00 input picofarads and 7.00 output picofarads

**Time Rating Per Characteristic:**

65.00 nanoseconds propagation delay time, low to high level output and 65.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Pal

**Test Data Document:**

82577-932906 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

28 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0