

View Online at <https://aerobasegroup.com/nsn/5962-01-123-7983>

Body Length:

0.440 inches

Body Width:

Between 0.245 inches and 0.300 inches

Body Height:

Between 0.045 inches and 0.085 inches

Maximum Power Dissipation Rating:

880.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and w/enable and resettable

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

7 input

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.0 volts power source

Time Rating Per Characteristic:

45.00 nanoseconds propagation delay time, low to high level output and 45.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

First-in first-out

Test Data Document:

82577-932893 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0