## NSN 5962-01-123-7984

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-123-7984 **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.085 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+175.0 degrees celsius **End Application:** Radar 76301 **Features Provided:** Burn in and high speed and w/clock and w/enable and w/reset and hermetically sealed and monolithic and negative outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form: Emitter-coupled logic Input Circuit Pattern:** 8 input **Design Function And Quantity:** 1 counter, binary **Case Outline Source And Designator:** F-5 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -8.0 volts power source **Time Rating Per Chacteristic:** 7.00 nanoseconds propagation delay time, low to high level output and 7.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 82577-932729 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 flat leads Shelf Life: N/a **Unit Of Measure:** 

Demilitarization: Yes - demil/mli

## NSN 5962-01-123-7984

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0