Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-123-8113

# Maximum Power Dissipation Rating:

730.0 milliwatts

#### **Operating Tempurature Range:**

-0.0/+70.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## Features Provided:

High speed and static operation and 3-state output

#### **Inclosure Material:**

Oxide

### Inclosure Configuration:

Dual-in-line

#### Output Logic Form:

Transistor-transistor logic

#### Input Circuit Pattern:

Dual 2 input

#### **Design Function And Quantity:**

1 generator, character

#### **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-20.0 volts power source and 0.3 volts power source

#### **Test Data Document:**

33214-139-361 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Terminal Type And Quantity:

24 printed circuit

### Shelf Life:

N/a

#### Unit Of Measure:

---

#### **Demilitarization:**

Yes - demil/mli

#### Fiig:

A458a0