NSN 5962-01-123-9412

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-123-9412

| Body Outside Diameter: |
|---|
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 600.0 milliwatts |
| Operating Tempurature Range: |
| 55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| 65.0/+150.0 degrees celsius |
| Features Provided: |
| Burn in |
| nclosure Material: |
| Metal |
| nclosure Configuration: |
| Can |
| nput Circuit Pattern: |
| 1 input |
| Design Function And Quantity: |
| 1 amplifier, operational, general purpose |
| Terminal Surface Treatment: |
| Tin |
| Test Data Document: |
| 15786-307847 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| 4458a0 |
| |
| |
| |
| |