## NSN 5962-01-124-0131

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-124-0131

View Online at https://aerobasegroup.com/nsn/5962-01-124-0131
Body Length:
Between 0.745 inches and 0.785 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.100 inches and 0.140 inches
Maximum Power Dissipation Rating:
490.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Target g n el fscm 76301
Features Provided:
Hermetically sealed and monolithic and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Triple 2 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Terminal Surface Treatment:
Solder
Product Name:
Amplifier, transconductance, operational single
Voltage Rating And Type Per Characteristic:
18.0 volts power source
Test Data Document:
76301-5-1752 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0