NSN 5962-01-124-6930



Digital Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-124-6930 **Body Length:** Between 0.660 inches and 0.786 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and retriggerable and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 multivibrator, monostable **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 40.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 printed circuit Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0